

## Nylon Cable Tie Product Specification

- **Material:** UL approved Nylon 6/6
- **Flammability:** UL 94V-2
- **Working Temp.:** -40°C to 85°C
- **Color:** stock in Natural & Black (other colors are also available)
- Made to comply with MIL-SPEC M20693B, tensile strength meet or exceed MIL-S 23190E standard
- **Remark:** Complete range, stable quality and low insertion
- UV Black(UV Resistant) outdoor use



ITEM NO.	L mm (in.)	W mm (in.)	MAX. DIA. mm	MIN. STRENGTH Kg (lbs)	PACKING
TSL-80-m	80(3.1 )	2.5 (0.10 )	15	8 (18)	100 PCS PER BAG
TSL-90-M	90(3.5 )		17		
TSL-100-M	102(4.0 )		19		
TSL-120-M	118(4.6 )		30		
TSL-140-M	140(5.5 )		34		
TSL-160-M	155(6.1 )		40		
TSL-200-M	196(7.7 )		50		
TSL-150-I	150(5.9 )	3.2 (0.13 )	35	18 (40)	
TSL-140-I	140(5.5 )	3.6 (0.14 )	34		
TSL-180-I	182(7.1 )		44		
TSL-200-I	202(8.0 )		50		
TSL-250-I	250(10.0 )		60		
TSL-300-I	302(11.8 )		77		
TSL-370-I	368(14.5 )		100		

Continued.....

ITEM NO.	L mm (in.)	W Mm(in.)	MAX. DIA.mm	MIN. STRENGTH Kg (lbs)	PACKAGE
TSL-120-S	120(4.7 )	4.8 (0.19 )	25	25 (50)	100 PCS PER BAG
TSL-160-S	160(6.3 )		40		
TSL-190-S	186(7.3 )		46		
TSL-200-S	200(7.9 )		50		
TSL-250-S	252(10.0 )		60		
TSL-290-S	286(11.3 )		75		
TSL-300-S	298(11.7 )		80		
TSL-370-S	368(14.5 )		100		
TSL-430-S	428(16.9 )		115		
TSL-150-LHD	152(6.0 )	7.6 (0.30 )	35	54 (120)	
TSL-200-LHD	202(8.0 )		48		
TSL-290-LHD	292(11.5 )		75		
TSL-370-LHD	368(14.5 )		100		
TSL-450-LHD	450(17.7 )		133		
TSL-540-LHD	540(21.3 )		160		
TSL-430-HD	425(17.0 )	8.8 (0.35 )	115	79 (175)	
TSL-530-HD	525(20.7 )		150		
TSL-710-HD	702(27.6 )		185		
TSL-770-HD	770(30.3 )		220		
TSL-800-HD	798(31.4)		230		
TSL-240-EHD	238(9.4 )	12.4 (0.51 )	48	114 (250)	
TSL-300-EHD	286(11.3 )		75		
TSL-400-EHD	392(15.4 )		105		
TSL-500-HD	498(19.6 )		140		
TSL-600-HD	598(23.5 )		160		
TSL-700-HD	702(27.6 )		185		
TSL-800-HD	802(32.0 )		232		